

Product Feature

Totalising function:

Each batch of product can be weighed multiple times, and finally accumulated to a total weight for avoiding overload.

Multiple function keys:

There are many function keys (including tare and gross weight), which can meet various weighing needs of customers.

Unit Switching:

The unit of weight can be freely switched between lb and kg to meet different needs of customers.

Big function keys that “click”:

When pressing the function keys, the operator senses a “click”movement. Even when working with gloves,the operator feels whether he has pressed the key properly.

Build-in Rechargeable Battery:

Built-in 4000mAH super-capacity rechargeable battery with the advantages of durability and convenient charging, without disassembly. It lasts 3 months on a single battery charge. and the operating current is only 1ma (on the premise that backlight and printer connection are turned off).



HPT20S
WEIGHING SCALE PALLET TRUCK

High Definition Display:

High definition of the LCD display. Display can be read from any angle and with backlight, it can be used in dark environment.

High Accuracy:

Maximum error 0.05% of four sensors with ultra-high consistency. Even if a load is placed out of centre or the floor conditions that are not optimal, the accuracy remains high.

Optional Printer:

Support external printer, you can convert the numerical data to paper label freely. Equipped with low voltage protection, even if the vehicle shakes, it will not affect the use of the printer.

		1KG=2.2LB	1inch=25.4mm
Manufacturer’s type designation		HPT20S	
Load capacity / rated load	Q (kg)	2000	
Load centre distance	c (mm)	600	620
Load distance ,centre of drive axle to fork	x (mm)	863	933
Wheelbase	y (mm)	1195	1265
Tyres: solid rubber, superelastic, pneumatic, polyurethane		PU / Rubber / Nylon	
Tire size,front	Øxw (mm)	Ø 180×50	
Tire size,rear	Øxw (mm)	Ø 74×70/74×93	
Wheels,number front/rear(x=driven wheels)		2/2 or 2/4	
Lift height	h3 (mm)	115	
Height of tiller in drive position min./ max.	h14 (mm)	1207	
Standing height, elevated	h23 (mm)	200	
Height, lowered	h13 (mm)	85	
Overall length	l1 (mm)	1569	1693
Overall width	b1 (mm)	557 / 692	
Fork dimensions	s/e/l (mm)	50 / 182 / 1150	50 / 182 / 1220
Width over forks	b5 (mm)	557 / 692	
Ground clearance, centre of wheelbase	m2 (mm)	26	
Aisle width for pallets 1000×1200 crossways	Ast (mm)	1833	1903
Aisle width for pallets 800×1200 lengthways	Ast (mm)	1833	1903
Turning radius	Wa (mm)	1346	1416
Battery voltage, nominal capacity K5	V / Ah	6V/4.5Ah	

